

CCECorded Contract System



## **Product information**

- Heavy duty cord operated system, with separate internal cord channels; preventing cord sag and eliminating cord tangle.
- Bendable; it can be curved and reversed curved with a 20 cm (8") radius or continuous curve.
- Heavy duty klickable carriers 10 carriers on a breakaway strip UV protected.
- Can also be used for Forest Easyfold and accordiafold drapery systems.
- Maximum fabric weight: 8 kg. per mtr (5,3 LBS per ft).
- Colours available: white, silver and brown.
- Track finish: chromated powder coating with a factory applied patented dry lubricant.
- Lengths available: 3.66 m (12'), 4.27 m (14'), 4.88 m (16'), 6.10 m (20').

### For use in

Hotels - motels - offices - healthcare - schools - residential or any location where a heavy duty cord traverse system is required.

# Applications



# Profile

Shown actual size 1:1 Aluminium Extrusion Weight: 300 gram per mtr (3.22 ounce per ft) Dimensions: 20 mm x 20 mm (3/4" x 3/4")



# Bending/curving

The track can be curved and reversed curved using a 20 cm (8") radius. Continuous curving can be done with the electric powered bender or by special order from factory.



1 Carrier 6 2 CCS/FMS Master Carrier Underlap ③ Traverse cord 3 (4) CCS/FMS Master Carrier Overlap 5 CCS Cord connector 6 CCS Track 7 Pulley 6 4 1 2 1 Easy installation click - position - tighten 38 mm (1/2") clickable carrier

# **Mounting Brackets**

#### Aluminium Wall Bracket single

A) 7,5 cm (3"): B) 6,3 cm (2")
A) 10 cm (4"): B) 8,8 cm (3")



### Aluminium Wall Bracket double

A) 15 cm (6"): B) 9,2 cm (3"), C) 4,5 cm (2") A) 20 cm (8"): B) 9,2 cm (3"), C) 9,5 cm (4")



### Aluminium Wall Bracket triple 25 cm (10")



Brackets need to placed every 50 - 60 cm (24"), depending on fabric weight.

Ceiling bracket

0



A) Min. 20 cm (8")



| Complete the a <b>01 White, 03</b> | able from stock:<br>art.nr. with the indicated colour-code<br><b>3 Silver, 05 Brown.</b><br>can be delivered on request.   |                            |             | <b>End Pulley Small</b><br>Reversible, for non-stacking side<br>on one way draw.<br>Colours: 01, 03, 05.   | 30302 000<br>25/box                               |
|------------------------------------|--|----------------------------|-------------|--|---|
|                                    | <b>CCS Track</b><br>Extruded aluminium chromated,<br>powder coated. Factory lubricated for<br>wall or ceiling mounting. Inches 3.66 m<br>(12'), 4.27 m. (14'), 4.88 m. (16'),<br>6.10 m. (20'). Colours: 01, 03, 05. | 30010cm<br>10/bundle<br>1. |             | <b>Inside Wall Bracket</b><br>For additional support anywhere the<br>pulley meets the wall.  | 3022301000<br>25/box                              |
|                                    | <b>CS/CCS/FMS CARRIER SMALL</b><br>Contract click carrier patented,<br>clickable. UV-resistant POM plastic.<br>Colours: 01, 03, 05.  | 25101 000<br>250/box       | Jose Marine | <b>Straight Return R/L</b><br>Adjustable from 7,5 cm (3")<br>to 25 cm (10").   | 3022501000<br>10/box                              |
|                                    | <b>FMS/CCS/MRS Wheel Carrier</b><br>The wheel carrier goes smoothly<br>over a splice.  | 5210101002<br>100/box      |             | <b>Traverse Cord</b><br>Nylon drapery cord designed for<br>strong smooth slide, Ø 3.5 mm<br>(0,14"),16 ply.<br>Colours: 01, 03.                        | 10304000<br>250 mtr/roll                          |
|                                    | <b>CS/CCS/FMS Track Joiner</b><br>Used to make a solid connection<br>between two pieces of track.<br>Colours 01, 03, 05.   | 25184000<br>10/box         | Jan B       | <b>Tension Pulley</b><br>Metal.<br>Colours: 01.  | 1030501000<br>25/box                              |
|                                    | <b>CCS Cord Master Carrier R/L</b><br><b>Underlap</b><br>Multifunctional - reversible arm<br>- will go through curves.<br>Colours: 01, 03.   | 3015601000<br>15/box       |             | <b>Cord Chain Weight Design</b><br>110 gr<br>White<br>Grey<br>Black  | 10/box<br>3030701000<br>3030703000<br>3030706000  |
|                                    | <b>CCS Cord Master Carrier R/L</b><br><b>Overlap</b><br>Multifunctional - reversible arm - will<br>through curves, will also fit stiffeners a<br>cord connector. Colours: 01, 03.                                    |                            |             | <b>Cord Safety Clip</b><br>Plastic.<br>Colours: 01.  | 3645702000<br>25/box                              |
|                                    | <b>CCS/FMS Master Carrier R/L</b><br><b>Underlap Single</b><br>Multifunctional - arm is reversible -<br>will slide trough curves.<br>Colours: 01, 03.  | 3016001000<br>15/box       |             | Smart Klick Ceiling Bracket<br>"Klicks" onto track, powder coated.<br>White included cover cap<br>Silver included cover cap<br>Brown include cover cap | 100/box<br>1018201001<br>1018203001<br>1018205001 |
|                                    | <b>CCS Cord Connector</b><br>Connects cord to the CCS master<br>carrier.<br>Colours: 01, 03, 05.   | 3030301000<br>100/box      |             | Smart Klick Double Ceiling<br>Bracket Large Distance between<br>two tracks: 90 mm (3,5")<br>Smart Klick Double<br>Ceiling Bracket Short                | 1018601000<br>30/box<br>1018611000<br>30/box      |
|                                    | <b>CCS Double Cord Connector</b><br>Connects cord to the CCS master<br>carrier.  | 3030301010<br>20/box       |             | Distance between two track<br>45 mm (1,8")<br>False Ceiling Bracket (metal)  | <s:<br>100/box<br/>4519001000</s:<br>             |
|                                    | Colours: 01, 03.<br><b>Pulley</b><br>Reversible, for two way draw.   | 30301 000<br>25/box        |             | For installation on to a suspended<br>ceiling. The track can be fixed in<br>any angle.   |   |
| 00                                 | Colours: 01, 03, 05.   |                            |             | <b>FSS Mounting Bracket</b><br>For concealed installation or ceiling<br>installation in narrow spaces.<br>Heavy Duty.                                  | 100/box<br>7160001000                             |
|                                    |  |                            |             |  |   |

|  |   | Adjustable Wall Bracket<br>Smart klick, adjustable single from<br>7,5 cm (3") to 11,5 cm (4.5")   | 10208115<br>100/box                            |  |  | <b>Bending Standard</b><br>Standard for Contract<br>bending tool   | 2560800000<br>1/each               |
|--|---|---|--|--|--|--|------------------------------------|
|  | to<br>Co<br>All<br>Sm<br>Co<br>Co<br>Co<br>Co<br>Co | to 10 cm (4") - 15 cm (6")<br>to 19,5 cm (7,5")<br>Colours: 01, 03.<br>Aluminium Wall Bracket<br>Smart klick, powder coated.  | 10208195<br>50/box<br>10203cm                  |  |  | <b>Electric Powered Bender</b><br>Available in 230V or 115V, to create<br>continuous curves and arches.<br>Minimum radius 50 cm (20"). | 1060500000<br>1/box                |
|  |   | 7,5 cm single         (3")           10 cm single         (4")           15 cm double         (6")           20 cm double         (8")           25 cm triple         (10") | 20/box<br>20/box<br>15/box<br>15/box<br>10/box |  |  | <b>Bending Wheels</b><br>For Electric Powered Bender.<br>Complete set of 3 wheels.   | 2560700000<br>1/set                |
|  |   | Colours: 01, 03.<br>Smart Klick Cover Cap   | 10213000<br>50/box<br>2560000000<br>1/each     |  |  | Electric Powered Railcutter<br>230 Volt EU<br>Replacement Blade<br>For electric powered railcutter.                                    | 1061100000<br>1061200000<br>1/each |
|  |   | Alu Wall Bracket Universal<br>Colours: 01, 03.<br>Contract Bending tool<br>For CS/CCS/FMS/CRS/MTS   |  |  | <b>Forest Lubricant</b><br>To lubricate components during<br>assembly. | 5109010000<br>1/box  |                                    |
|  |   | CS/CCS/FMS Bending Wheel  | 2561000000<br>1/each                           |  | Distributeur:  |  |                                    |
|  |   | <b>CCS Bending Strips</b><br>For CCS track, length: 90 cm (35,4")<br>For CCS electric powered bender.<br>Length 7 meter (23').  | 850000002<br>1/set<br>8500000010<br>1/each     |  |  |  |                                    |



